


PowerWise® 1G 4PPoE with FEP Jacket

CMP-LP



PRODUCT DESCRIPTION

FIRST MANUFACTURER IN THE INDUSTRY
to offer products that contribute toward LEED!

PowerWise® 1G 4PPoE cables provide the best performance and overall value for 4 Pair Power over Ethernet (4PPoE) applications requiring up to 100W of power and up to 1 Gigabit Ethernet performance. PowerWise 1G 4PPoE cables are specifically designed to mitigate temperature build-up, offer exceptional energy efficiency and ensure performance (up to 1 Gigabit Ethernet) over the lifetime of your system.

PowerWise 1G 4PPoE cable provides the performance benefits of a typical CAT 5E cable including a small diameter. Cable temperature increases are reduced and power efficiency is increased as a result of 22 gauge conductors. Plenum rated conductors are also 100% FEP insulated and ensure cable performance over the life of your system. Employing the latest polymer technology, FEP Jacketed Plenum is constructed entirely of chemical, oil, heat, and moisture resistant FEP fluoropolymer. It is ideally suited for industrial UTP applications where severe environmental stresses would compromise standard PVC plenum cables. Additionally, the cable is specially processed to ensure a more durable print legend. PowerWise 1G 4PPoE cables are the best solution to connect and power your 4PPoE applications compared to standard CAT 5e and 6 designs.

APPLICATIONS

- 10BASE-T through 1000BASE-T Ethernet
- Power over Ethernet (PoE) – IEEE 802.3af
- PoE+ – IEEE 802.3at Type 1 and 2
- 4PPoE – IEEE 802.3bt Type 3 and 4 draft D1.2
- ATM and token ring
- HDBaseT Class A and B

FEATURES

- Guaranteed 0.3 dB headroom for IL, ACR and PSACR
- Tested 350 MHz
- Tested in most severe temperature conditions in bundle of 100 cables
- CableID® alpha numeric code printed every 2 feet
- QuickCount® marking system in feet and meters
- ColorTip® circuit identification system
- Color coded box labels
- HDBaseT Class A and B certified
- UL LP listed
- FEP Jacket
- All fluoropolymer construction

BENEFITS

- Performance assurance for exceptional overall channel performance
- Assures ample bandwidth Headroom
- AWG 22 insulated wire offers 88% power efficiency and lowest temperature increase inside a bundle, the best of its class
- Allows both ends of a cable run to be easily identifiable without the need to separately label or tone the cable
- Provides remaining length of cable on reel
- Easily identifiable conductor mates even in low-light environments
- Easily identifies jacket colors
- Ideal for any A/V applications up to 100m channel
- Third-party assurance of product safety in high-heat and high-power applications
- Lower smoke emission in plenum test than PVC
- Resistant to chemical, moisture, thermal exposure

SPECIFICATIONS

Pair Count	4
Conductor	Solid annealed copper
AWG (mm)	22 (0.64)
Insulation	CMP: FEP
Insulation Colors	Pair 1: ColorTip Light Blue, Blue Pair 2: ColorTip Light Orange, Orange Pair 3: ColorTip Light Green, Green Pair 4: ColorTip Light Brown, Brown
Jacket	Low Smoke FEP
Characteristic Impedance Ohms	100 ± 15
Nominal Velocity of Propagation %	CMP: 74
Performance Compliance	UL 444 NFPA 262 ANSI/TIA-568.2-D HDBaseT Class A and B
NRTL Programs	UL Verified CAT 5e UL Listed CMP-LP (0.6) c(UL) Listed CMP HDBaseT Certified

ENVIRONMENTAL SPECIFICATIONS

Operation	-40°C to +200°C
Storage/Shipping	-40°C to +200°C
Installation	-40°C to +200°C

PART NUMBERS AND PHYSICAL CHARACTERISTICS

Listing	Part Number ¹	Nominal Diameter in (mm)	Approx. Weight lbs/kft (kg/km)	Package	Packages per Pallet
CMP	PW52-H72-xP	0.23 (5.8)	37 (55)	1,000 ft Plywood Reel	20

JACKET COLORS

¹ Replace "x" with:	Blue = 2	Gray = 3	White = 4	Green = 5	Yellow = 6	Purple = 7	Red = 9	Black = E
--------------------------------	----------	----------	-----------	-----------	------------	------------	---------	-----------

ELECTRICAL SPECIFICATIONS

Frequency MHz	Insertion Loss @ 20°C Maximum dB/100 m			NEXT Minimum dB/100 m		ACR Minimum dB/100 m			PSNEXT Minimum dB/100 m	
	TIA-568.2-D	Superior Essex		TIA-568.2-D	Superior Essex	TIA-568.2-D	Superior Essex		TIA-568.2-D	Superior Essex
	Specified	Guaranteed	Typical	Specified	Typical	Calculated	Guaranteed	Typical	Specified	Typical
1	2	1.7	1.7	65.3	76.8	63.3	63.6	81.0	62.3	75.3
4	4.1	3.8	3.7	56.3	67.8	52.2	52.5	70.1	53.3	66.3
8	5.8	5.5	5.4	51.8	63.3	46.0	46.3	63.9	48.8	61.8
10	6.5	6.2	6.0	50.3	61.8	43.8	44.1	61.8	47.3	60.3
16	8.2	7.9	7.7	47.2	58.7	39.0	39.3	57.0	44.3	57.2
20	9.3	9.0	8.6	45.8	57.3	36.5	36.8	54.7	42.8	55.8
25	10.4	10.1	9.6	44.3	55.8	33.9	34.2	52.2	41.3	54.3
31.25	11.7	11.4	10.8	42.9	54.4	31.2	31.5	49.6	39.9	52.9
62.5	17	16.7	15.5	38.4	49.9	21.4	21.7	40.4	35.4	48.4
100	22	21.7	19.8	35.3	46.8	13.3	13.6	33.0	32.3	45.3
155			24.8		43.9			25.1		42.4
200			28.2		42.3			20.1		40.8
250			31.8		40.8			15.0		39.3
300			35		39.6			10.6		38.1
350			38.3		38.6			6.3		37.1

Frequency MHz	PSACR Minimum dB/100 m			Return Loss Minimum dB/100 m		ELFEXT Minimum dB/100 m		PSELFEXT Minimum dB/100 m	
	TIA-568.2-D	Superior Essex		TIA-568.2-D	Superior Essex	TIA-568.2-D	Superior Essex	TIA-568.2-D	Superior Essex
	Calculated	Guaranteed	Typical	Specified	Typical	Specified	Typical	Specified	Typical
1	60.3	60.6	78.3	20.0	33.0	63.8	74.6	60.8	69.3
4	49.2	49.5	67.4	23.0	36.0	51.8	62.6	48.8	57.3
8	43.0	43.3	61.2	24.5	37.5	45.7	56.5	42.7	51.2
10	40.8	41.1	59.1	25.0	38.0	43.8	54.6	40.8	49.3
16	36.1	36.4	54.3	25.0	38.0	39.7	50.5	36.7	45.2
20	33.5	33.8	52.0	25.0	38.0	37.8	48.6	34.8	43.3
25	30.9	31.2	49.5	24.3	37.3	35.8	46.6	32.8	41.3
31.25	28.2	28.5	46.9	23.6	36.6	33.9	44.7	30.9	39.4
62.5	18.4	18.7	37.7	21.5	34.5	27.9	38.7	24.9	33.4
100	10.3	10.6	30.3	20.1	33.1	23.8	34.6	20.8	29.3
155			22.4		31.8		30.8		25.5
200			17.4		31.0		28.6		23.3
250			12.3		30.3		26.6		21.3
300			7.9		29.8		25.1		19.8
350			3.6		29.3		23.7		18.4