



# Panel Interface Connectors

## Popular PIC Models



Standard Metal Housing | UL Type 4, 4X, 12 | IP65 Rating

Part Number	Description	Faceview	Part Number	Description	Faceview
GF-R-32	GFCI Receptacle 3 AMP Reset Size 32 Housing		DP1-DB9M-16LS	Single Outlet 9 Pin D-Sub Male Exterior/Male Interior Size 16 Housing	
GF-RJ45-USB-BFAF-32	GFCI Receptacle RJ45 USB Female Form B to Female Form A Size 32 Housing		DP-RJ45S-USB-BFAF-R-32	Duplex Receptacle Shielded RJ45 USB Female Form B to Female Form A 3 AMP Reset Size 32 Housing	
DCH1-RJ45-R-32	China 10 AMP Receptacle RJ45 3 AMP Reset Size 32 Housing		D-BNC-2-10LS	2 x BNC Size 10 Housing	
RJ11-06LS	RJ11 Size 06 Housing		DP1-USB-BFAF-16LS	Single Outlet USB Female Form B to Female Form A Size 16 Housing	
DB09-2RJ45-16LS	9 Pin D-Sub 2 x RJ45 Size 16 Housing		DUK-RJ45-R-32	UK Receptacle RJ45 3 AMP Reset Size 32 Housing	
RJ45-2USB-*-24	RJ45 2 x USB Form A Female with Cable to USB Form A Male Size 24 Housing		DP-RJ11-RJ45-R-32	Duplex Receptacle RJ11 RJ45 3 AMP Housing Size 32 Housing	
GF-DB9F-RJ45-R-32	GFCI Receptacle 9 pin D-Sub Female Exterior/Female Interior RJ45 3 AMP Reset Size 32 Housing		RJ45-USB-*-10LS	RJ45 USB Form A Female with Cable to USB Form A Male Size 10 Housing	
D-USB-16LS	2 x USB A connections Size 16 Housing		DP1-06LS	Single Outlet Size 06 Housing	
GF-2RJ45-5R-32	GFCI Receptacle 2 x RJ45 5 AMP Reset Size 32 Housing		DP1-RJ11-2RJ45-R-32	Single Outlet RJ11 2 x RJ45 3 AMP Reset Size 32 Housing	

\* Length in feet. Standard cable lengths are 3,6 & 10 feet. Consult factory for other lengths.

PICs with International outlets are non-UL.