



# Panel Interface Connectors

*Other Popular Models*



Other Versions | Standard Metal Housing | DIN Rail | UL Type 4, 4X, 12 | IP65 Rating



| Part Number                                 | Description   |
|---|---|
| <b>DIN Rail Mounted (For Inside Panels)</b> |   |
| DB9-TS                                      | 9 Pin D-sub, DIN Rail Mount   |
| DP1-RJ45-TS                                 | Single Outlet Receptacle, RJ45, DIN Rail Mount  |
| DP-TS                                       | Duplex Receptacle, DIN Rail Mount   |
| <b>Ethernet</b>                             |   |
| RJ45-4-24LS                                 | 4 x RJ45, Size 6 Housing  |
| RJ45C-2-10LS                                | 2 x RJ45 with Punchdown, Size 10 Housing  |
| <b>USB</b>                                  |   |
| D-2USB-AFAF-2RJ45-24LS                      | 2xUSB Form A Female to Female, 2 x RJ45, Size 24 Housing  |
| D-USB-*-PL06                                | USB Form A Female with Cable to USB Form A Male, Size 6 Plate   |
| D-USBBB-*-06LS                              | USB Form B Female to Form B Male Cable, Size 6 Housing  |
| D-USB-RJ45-24LS                             | 2 x USB Form A, RJ45, Size 24 Housing   |
| <b>Others</b>                               |   |
| DFD-24LS-KIT                                | Housing and Bracket for Mounting 3-1/2 Bay Unit (Floppy Drives, Zip Drives, Jazz Drives, etc.), Drives Not Included |
| D-FOPT-12                                   | Fiber Optic Connector, 1/2-14 NPT Shell   |
| D-HDMI-**-06LS                              | HDMI Male/Female Cable, Size 6 Housing  |
| DMC-RJ45-R-16                               | C14 Male Receptacle IEC, RJ45, 3 AMP Reset, Size 16 Housing   |
| IEC-2-GF-48                                 | 2 x C13 Female Receptacles IEC with GFCI, Size 48 Housing   |

\* Length in feet. Standard cable lengths are 3,6 & 10 feet. Consult factory for other lengths.

\*\* Length in meters.