



B

B

A device employing a 15 A or 20 A grounding type receptacle but no supplementary protector shall be protected by a fuse or circuit breaker that does not exceed the marked rating of the receptacle in the end use. When a fuse or circuit breaker rated less than the receptacle's rating is provided, a Marking shall be provided to indicate the maximum ampere rating of the protection provided.

PIC RATINGS/SPECIFICATIONS	
VOLTS:	125V
AMPS:	15A
SCCR:	10kA

HOUSING MATERIALS	
PLATE:	16 GA 304 STAINLESS STEEL

OPERATING TEMPERATURE: (-10°C / +60°C (+14°F / +140°F))

cRaus[®]

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES AND [MM]	DRAWN BY	DCG	MATERIAL		MENCOM CORPORATION
	DRAWN DATE	08/16/2021			TITLE:
	CHECKED BY	DCG			GFI; RJ45; USB-AA; 32; PLT ONLY
	CHECK DATE	08/18/2021			
COMMENTS:					
SIZE	DWG. NO.				
B	GF-RJ45-USB-AFAF-PL32				REV C
SCALE: 1:1	WEIGHT:				SHEET 1 OF 1

STANDARD CONFIGURATIONS UNLESS OTHERWISE NOTED		
CONN. TYPE	EXTERIOR	INTERIOR
RJ45	CAT. 6 JACK	CAT. 6 JACK

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
MENCOM CORPORATION. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
MENCOM CORPORATION IS
PROHIBITED.
