



These devices shall be mounted on enclosures having adequate strength and thickness and with adequate spacing provided. Seal rating is based on mounting to a surface that is clean, flat and smooth.

HOUSING MATERIALS		PIC RATINGS/SPECIFICATIONS	
BODY:	EPOXY COATED DIE CAST ALUMINUM	NEMA/UL EN 60529:	4, 4X, 12 IP65
GASKET:	THERMOPLASTIC ELASTOMER	MOUNTING SCREW SIZE:	M4 (8-32) (304 or 316SS for 4X)
HANDLE:	POLYAMIDE	MOUNTING SCREW TORQUE:	1.2~1.8N·m (0.9~1.3 Lb·Ft)
LEVERS:	STAINLESS STEEL		



LISTED
ENCL. ACC.
5JR2

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES
AND [MM]

DRAWN BY DCG
DRAWN DATE 08/05/2020
CHECKED BY GO
CHECK DATE 08/05/2020

COMMENTS:

MENCOM CORPORATION

TITLE:
RJ45; 1/2NPT; 06 SFS MNT

SIZE DWG. NO.
B RJ45-P406 REV **C**
SCALE: 1:1 WEIGHT: SHEET 1 OF 1

MOUNTING KIT ORDERED
SEPARATELY CONTAINS
M5x0.8 SS SCREW, NYLON WASHER,
SPLIT LOCKWASHER AND M5 NUT
P/N: D-PIC-MT-M5

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
MENCOM CORPORATION. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
MENCOM CORPORATION IS
PROHIBITED.

STANDARD CONFIGURATIONS UNLESS OTHERWISE NOTED		
CONN. TYPE	EXTERIOR	INTERIOR
RJ45	CAT 6 JACK	CAT 6 JACK